



### STANDARD LAYBACK POST

SIZE	S (51)	M (54)	L (56)	XL (59)
1 Reach (mm)	380	395	405	425
2 Stack (mm)	505	516	526	527
3 Bottom Bracket Drop (mm)	72	72	72	72
4 Chainstay (mm)	395	395	395	395
5 Head Tube Angle (°)	71.5	72	72	72.5
6 Front-Center (mm)	575	589	602	621
7 Wheelbase (mm)	961	975	988	1007
8 Head Tube (mm)	100	110	120	120
9 Seat Tube Angle (Forward Setting, °)	77	77.5	78	78.5
10 Effective Top Tube (Forward Setting, mm)	495	505	515	531
11 Seat Tube Angle (Rearward Setting, °)	73	73.5	74	74.5
12 Effective Top Tube (Rearward Setting, mm)	532	541	552	656

### ZERO LAYBACK POST

SIZE	S (51)	M (54)	L (56)	XL (59)
1 Reach (mm)	380	395	405	425
2 Stack (mm)	505	516	526	527
3 Bottom Bracket Drop (mm)	72	72	72	72
4 Chainstay (mm)	395	395	395	395
5 Head Tube Angle (°)	71.5	72	72	72.5
6 Front-Center (mm)	575	589	602	621
7 Wheelbase (mm)	961	975	988	1007
8 Head Tube Length (mm)	100	110	120	120
9 Seat Tube Angle (Forward Setting, °)	81.5	82	82.5	83
10 Effective Top Tube (Forward Setting, mm)	452	463	474	491
11 Seat Tube Angle (Rearward Setting, °)	77.5	78	78.5	79
12 Effective Top Tube (Rearward Setting, mm)	488	497	508	524